


# 5M-S88+55CM-785-90-Q06-A8-C-6

Compact Laser Micro Focus Generator with elliptical Gaussian beam profile



#### **FEATURES**

Compact Laser spot with elliptical Gaussian beam profile.

■ Spot diameter: 0.023 x 0.041 mm

Wavelength: 785 nmWorking distance: 82 mm

 Micro Focus Generator for small spot widths and high power density in the focal plane



### **DESCRIPTION**

The laser diode beam source type 5M-S88+55CM-785-90-Q06-A8-C-6 produces an elliptical laser spot with elliptical Gaussian intensity distribution.

The laser has integrated electronics  $\underline{type\ C}$  for control of the laser output power. The output power can be controlled using the  $\underline{modulation\ input\ ports\ (TTL\ and\ analog)}}$  or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that the spot diameter increases proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

### **TECHNICAL DATA**

5M-S88+55CM-785-90-Q06-A8-C-6

Series 5M



Line profile	Gaussian Inter	nsity Distribution	
		Gaussian Intensity Distribution	
Wavelength	785 +10/-10 nm		
Laser output power	90 mW		
Laser safety class	3B		
Focussing range	70-125 mm		
Working distance	82 mm		
Spot height	0.041 mm		
Spot width	0.023 mm		
Rayleigh range	1.1 mm		
Diameter laser module	25/28 mm		
Module length	73.1 mm		
Installation length	185.1 mm		
Cable length	1.5 m		
Connector type	Lumberg SV50 IEC 61076-2-106		
Supply voltage	5 ± 0.2 V		
Max. current consumption	0.25 A		
Working temperature	0 - 40 °C		
Modulation inputs	Analog	TTL	
Input resistance	22 kOhm	22 kOhm	
Max. modulation frequency	100 kHz	100 kHz	
Modulation delay ON/OFF	1/0.5 µs	2/1 μs	
Rise / Fall time	3/2 µs	3/2 µs	

# **ACCESSORIES**

**60EX-4** Eccentric key with a stroke of  $\pm$  0.5 mm.

**60EX-4-L** Alternative eccentric key with long handle with a

stroke of ± 0.5 mm.

**9D-12** Screwdriver WS 1.2

# **RELATED PRODUCTS**



LASER MODULES

Compact Laser Macro Focus Generator

**SERIES 5MM** 

Circular beam profile andExtended depth of focus

LASER MODULES

Micro Focus Generator

**SERIES 13MC** 

Rotationally symmetric, Gaussian beam profile

LASER MODULES

Compact Laser Micro Focus Generator

**SERIES 5MC** 

Rotationally symmetric, Gaussian beam profile

LASER MODULES

Micro Focus Generator

**SERIES 13M** 

Elliptical Gaussian beam profile

This is a printout of the page <a href="https://sukhamburg.com/products/details/5M-S88">https://sukhamburg.com/products/details/5M-S88</a> 55CM-785-90-Q06-A8-C-6 from 5/8/2024

### CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

## **LEGAL NOTICE**

### Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]