

### 5MC-S150+29CM-635-11-B07-M12-S-6

Compact Laser Micro Focus Generator with rotationally symmetric beam profile



#### **FEATURES**

Compact laser spot with rotationally symmetric, Gaussian beam profile.

■ Spot diameter: 0.043 x 0.043 mm

Wavelength: 635 nmWorking distance: 147 mm

 Micro Focus Generator for small spot widths and high power density in the focal plane



### **DESCRIPTION**

The laser diode beam source type 5MC-S150+29CM-635-11-B07-M12-S-6 produces a rotationally symmetric circular laser spot with Gaussian intensity distribution.

The laser has integrated electronics <u>type S</u> for control of the laser output power. The output power can be controlled using the <u>modulation input ports (TTL and analog)</u> or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that the spot diameter increases proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

### **TECHNICAL DATA**

5MC-S150+29CM-635-11-B07-M12-S-6

Series 5MC



Line profile  Wavelength  Laser output power  Laser safety class  Focussing range  Working distance  Spot height  Spot width  Rayleigh range  Diameter laser module  Module length	Gaussian Inte	11 mW 3B 125-260 mm	
Laser output power  Laser safety class  Focussing range  Working distance  Spot height  Spot width  Rayleigh range  Diameter laser module		11 mW 3B 125-260 mm	
Laser safety class  Focussing range  Working distance  Spot height  Spot width  Rayleigh range  Diameter laser module		3B 125-260 mm	
Focussing range Working distance Spot height Spot width Rayleigh range Diameter laser module		125-260 mm	
Working distance  Spot height  Spot width  Rayleigh range  Diameter laser module			
Spot height Spot width Rayleigh range Diameter laser module		1.47 mm	
Spot width Rayleigh range Diameter laser module		147 mm	
Rayleigh range Diameter laser module	0.043 mm		
Diameter laser module	0.043 mm		
	4.51 mm		
Module length	12 mm		
	65.2 mm		
Installation length	242.2 mm		
Cable length	1.5 m		
Connector type Lum	Lumberg SV50 IEC 61076-2-106		
Supply voltage	5 ± 0.25 V		
Max. current consumption	0.25 A		
Working temperature		0 - 40 °C	
Modulation inputs	Analog	TTL	
Input resistance	22 kOhm	22 kOhm	
Max. modulation frequency	50 kHz	1000 kHz	
Modulation delay ON/OFF	4/0.5 μs	0.05/0.05 μs	
Rise / Fall time	σ.σ μο		

## **ACCESSORIES**

**60EX-4** Eccentric key with a stroke of  $\pm$  0.5 mm.

**60EX-4-L** Alternative eccentric key with long handle with a

stroke of  $\pm$  0.5 mm.

**9D-12** Screwdriver WS 1.2

PS051003E Power Supply 5 V

# **RELATED PRODUCTS**



LASER MODULES

Compact Laser Micro Focus Generator

**SERIES 5M** 

Elliptical Gaussian beam profile

LASER MODULES

Micro Focus Generator

**SERIES 13MC** 

Rotationally symmetric, Gaussian beam profile

LASER MODULES

Micro Focus Generator

**SERIES 13M** 

Elliptical Gaussian beam profile

This is a printout of the page <a href="https://sukhamburg.com/products/details/5MC-S150">https://sukhamburg.com/products/details/5MC-S150</a> 29CM-635-11-B07-M12-S-6 from 4/25/2024

### CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

### **LEGAL NOTICE**

#### Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]