

5MC-S88+29CM-635-11-B07-M12-S-6

Compact Laser Micro Focus Generator with rotationally symmetric beam profile



FEATURES

Compact laser spot with rotationally symmetric, Gaussian beam profile.

■ Spot diameter: 0.025 x 0.025 mm

Wavelength: 635 nmWorking distance: 82 mm

 Micro Focus Generator for small spot widths and high power density in the focal plane



DESCRIPTION

The laser diode beam source type 5MC-S88+29CM-635-11-B07-M12-S-6 produces a rotationally symmetric circular laser spot with Gaussian intensity distribution.

The laser has integrated electronics <u>type S</u> for control of the laser output power. The output power can be controlled using the <u>modulation input ports (TTL and analog)</u> or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that the spot diameter increases proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

5MC-S88+29CM-635-11-B07-M12-S-6

Series 5MC



Wavelength Laser output power Laser safety class Focussing range Working distance Spot height Spot width Rayleigh range Diameter laser module Module length Installation length Cable length	ensity Distribution 635 +8/-8 nm 11 mW 3B 70-125 mm 82 mm 0.025 mm	
Laser output power Laser safety class Focussing range Working distance Spot height Spot width Rayleigh range Diameter laser module Module length Installation length Cable length Connector type Lumberg SV50 II	11 mW 3B 70-125 mm 82 mm	
Laser safety class Focussing range Working distance Spot height Spot width Rayleigh range Diameter laser module Module length Installation length Cable length Connector type Lumberg SV50 II	3B 70-125 mm 82 mm	
Focussing range Working distance Spot height Spot width Rayleigh range Diameter laser module Module length Installation length Cable length Connector type Lumberg SV50 II	70-125 mm 82 mm	
Working distance Spot height Spot width Rayleigh range Diameter laser module Module length Installation length Cable length Connector type Lumberg SV50 II	82 mm	
Spot height Spot width Rayleigh range Diameter laser module Module length Installation length Cable length Connector type Lumberg SV50 II		
Spot width Rayleigh range Diameter laser module Module length Installation length Cable length Connector type Lumberg SV50 II	0.025 mm	
Rayleigh range Diameter laser module Module length Installation length Cable length Connector type Lumberg SV50 II		
Diameter laser module Module length Installation length Cable length Connector type Lumberg SV50 II	0.025 mm	
Module length Installation length Cable length Connector type Lumberg SV50 II	1.55 mm	
Installation length Cable length Connector type Lumberg SV50 II	12 mm	
Cable length Connector type Lumberg SV50 II	65.2 mm	
Connector type Lumberg SV50 II	177.2 mm	
-	1.5 m	
Supply voltage	IEC 61076-2-106	
	5 ± 0.25 V	
Max. current consumption	0.25 A	
Working temperature	0 - 40 °C	
Modulation inputs Analog	TTL	
Input resistance 22 kOhm	22 kOhm	
Max. modulation frequency 50 kHz	1000 kHz	
Modulation delay ON/OFF 4/0.5 μs	0.05/0.05 μs	
Rise / Fall time 5/4 μs	0.1/0.02 μs	

ACCESSORIES

60EX-4 Eccentric key with a stroke of \pm 0.5 mm.

60EX-4-L Alternative eccentric key with long handle with a

stroke of ± 0.5 mm.

9D-12 Screwdriver WS 1.2

PS051003E Power Supply 5 V

RELATED PRODUCTS



LASER MODULES Compact Laser Micro Focus Generator

SERIES 5M • Elliptical Gaussian beam profile

LASER MODULES • Micro Focus Generator

SERIES 13MC • Rotationally symmetric, Gaussian beam profile

LASER MODULES

• Micro Focus Generator

SERIES 13M • Elliptical Gaussian beam profile

This is a printout of the page $\underline{\text{https://sukhamburg.com/products/details/5MC-S88}}$ 29CM-635-11-B07-M12-S-6 from 4/17/2024

CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]