#### 5MC-S88+29CM-658-24-B09-M12-S-6

Compact Laser Micro Focus Generator with rotationally symmetric beam profile



#### FEATURES

Compact laser spot with rotationally symmetric, Gaussian beam profile.

- Spot diameter: 0.026 x 0.026 mm
- Wavelength: 658 nm
- Working distance: 82 mm
- Micro Focus Generator for small spot widths and high power density in the focal plane



## DESCRIPTION

The laser diode beam source type 5MC-S88+29CM-658-24-B09-M12-S-6 produces a rotationally symmetric circular laser spot with Gaussian intensity distribution.

The laser has integrated electronics <u>type S</u> for control of the laser output power. The output power can be controlled using the <u>modulation input ports (TTL and analog)</u> or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that the spot diameter increases proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

## **TECHNICAL DATA**

5MC-S88+29CM-658-24-B09-M12-S-6

Series

5MC



## **DATA SHEET**

Laser output power         Laser safety class         Focussing range       70         Working distance         Spot height       0         Spot width       0         Rayleigh range       0         Diameter laser module       0         Module length       1         Cable length       1         Cable length       1         Connector type       Lumberg SV50 IEC 610	+5/-5 nm 24 mW 3B -125 mm 82 mm
Laser output power         Laser safety class         Focussing range       70         Working distance         Spot height       0         Spot width       0         Rayleigh range       0         Diameter laser module       0         Module length       1         Cable length       1         Cable length       1         Connector type       Lumberg SV50 IEC 610	24 mW 3B -125 mm
Laser safety class         Focussing range       70         Working distance       70         Spot height       0         Spot width       0         Rayleigh range       0         Diameter laser module       0         Module length       1         Cable length       1         Cable length       1         Connector type       Lumberg SV50 IEC 610	3B -125 mm
Focussing range       70         Working distance       0         Spot height       0         Spot width       0         Rayleigh range       0         Diameter laser module       0         Module length       1         Cable length       1         Connector type       Lumberg SV50 IEC 610	-125 mm
Working distance         Spot height       0         Spot width       0         Rayleigh range       0         Diameter laser module       0         Module length       1         Installation length       1         Cable length       1         Connector type       Lumberg SV50 IEC 610	
Spot height       0         Spot width       0         Rayleigh range       0         Diameter laser module       0         Module length       1         Installation length       1         Cable length       1         Connector type       Lumberg SV50 IEC 610	82 mm
Spot width       0         Rayleigh range       0         Diameter laser module       0         Module length       1         Installation length       1         Cable length       1         Connector type       Lumberg SV50 IEC 610	
Rayleigh range         Diameter laser module         Module length         Installation length         Cable length         Connector type	.026 mm
Diameter laser module         Module length         Installation length         Cable length         Connector type         Lumberg SV50 IEC 610	.026 mm
Module length         Installation length       1         Cable length         Connector type       Lumberg SV50 IEC 610	1.61 mm
Installation length     1       Cable length     1       Connector type     Lumberg SV50 IEC 610	12 mm
Cable length Connector type Lumberg SV50 IEC 610	65.2 mm
Connector type Lumberg SV50 IEC 610	77.2 mm
	1.5 m
Supply voltage	76-2-106
Supply voltage 5	± 0.25 V
Max. current consumption	0.25 A
Working temperature	0 - 40 °C
Modulation inputs Analog	TTL
Input resistance 22 kOhm 2	22 kOhm
Max. modulation frequency50 kHz1	.000 kHz
Modulation delay ON/OFF4/0.5 μs0.05	5/0.05 μs
Rise / Fall time         5/4 μs         0.2	

## ACCESSORIES

60EX-4	Eccentric key with a stroke of $\pm$ 0.5 mm.
60EX-4-L	Alternative eccentric key with long handle with a stroke of $\pm$ 0.5 mm.
9D-12	Screwdriver WS 1.2
PS051003E	Power Supply 5 V

## **RELATED PRODUCTS**





LASER MODULES SERIES 5M	<ul> <li>Compact Laser Micro Focus Generator</li> <li>Elliptical Gaussian beam profile</li> </ul>
LASER MODULES SERIES 13MC	<ul> <li>Micro Focus Generator</li> <li>Rotationally symmetric, Gaussian beam profile</li> </ul>

LASER MODULES SERIES 13M

- Micro Focus Generator
- Elliptical Gaussian beam profile

This is a printout of the page <u>https://sukhamburg.com/products/details/5MC-S88\_29CM-658-24-B09-M12-S-6</u> from 4/25/2024

## CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

# LEGAL NOTICE

#### Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]

