

### 5MM-S50-0.8+25CM-405-5-Y07-A4.5-B-4

Compact Laser Macro Focus Generator with approx. circular beam profile



#### **FEATURES**

Compact Laser spot with approx. circular beam profile and extended depth of focus.

Spot diameter: 0.043 x 0.042 mm

Wavelength: 405 nmWorking distance: 46 mmDepth of focus: 7.05 mm

Macro Focus Generator for extended depth of focus



### DESCRIPTION

The laser diode beam source type 5MM-S50-0.8+25CM-405-5-Y07-A4.5-B-4 produces a circular laser spot with extended depth of focus. The beam profile is approx. Gaussian. More precisely it has an elliptical intensity distribution clipped by a circular aperture.

The laser has integrated electronics  $\underline{type\ B}$  for control of the laser output power. The output power can be controlled using the  $\underline{modulation\ input\ port\ (TTL)}$  or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that the spot diameter increases proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

### **TECHNICAL DATA**

5MM-S50-0.8+25CM-405-5-Y07-A4.5-B-4



Series	5MM
Order Code	5MM-S50-0.8+25CM-405-5-Y07-A4.5-B-4
Line profile	Gaussian Intensity Distribution
Wavelength	405 +5/-5 nm
Laser output power	5 mW
Laser safety class	3R
Focussing range	35-70 mm
Working distance	46 mm
Spot height	0.042 mm
Spot width	0.043 mm
Depth of focus	7.05 mm
Diameter laser module	12 mm
Module length	65.4 mm
Installation length	141.4 mm
Cable length	1.5 m
Connector type	Lumberg SV40 IEC 61076-2-106
Supply voltage	12 ± 0.5 V
Max. current consumption	0.16 A
Working temperature	0 - 40 °C
Modulation inputs	TTL
Input resistance	110 kOhm
Max. modulation frequency	0.2 kHz
Modulation delay ON/OFF	500/500 μs
Rise / Fall time	10/20 μs

# **ACCESSORIES**

**60EX-4** Eccentric key with a stroke of  $\pm$  0.5 mm.

**60EX-4-L** Alternative eccentric key with long handle with a

stroke of ± 0.5 mm.

**9D-12** Screwdriver WS 1.2

PS120516E Power Supply 12 V

# **RELATED PRODUCTS**



**LASER MODULES** 

**SERIES 5M** 

Compact Laser Micro Focus Generator

Elliptical Gaussian beam profile

LASER MODULES

Laser Macro Focus Generator

SERIES 13MMC

Rotationally symmetric beam profile

Extended depth of focus

LASER MODULES

SERIES 13MM

Macro Focus Generator

• Circular beam profile

Extended depth of focus

This is a printout of the page <a href="https://sukhamburg.com/products/details/5MM-S50-0">https://sukhamburg.com/products/details/5MM-S50-0</a> 8 25CM-405-5-Y07-A4 5-B-4 from 4/25/2024

### **CONTACT**

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

## **LEGAL NOTICE**

### Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]