5PF-C-400-S

Polarization beam splitter cube (short version)



FEATURES

Polarization filter with system mount \emptyset 8 mm for attaching to <u>60FC</u> Fiber Collimators (with outer diameter \emptyset 12 mm).

This filter transmits only the linear polarized component of the radiation.

- Polarization beam splitter cube with deflection of the unwanted orthogonally polarized radiation
- Polarization extinction ratio 10.000:1
- Surface deviation < λ/4
- Clear aperture: 4 mm
- System mount: Ø 8 mm
- AR Coating: 390 480 nm
- Short Version without front fitting

TECHNICAL DATA

5PF-C-400-S

Order Code	5PF-C-400-S
Туре	Polarizing cube beam splitter
Wavelength range	390 - 480 nm (residual reflectivity < 1.5 %)
Extinction	10.000:1
Transmission	> 95 %
AR Coating	yes
Surface deviation	< \\/4
Clear aperture	4 mm
System mount	Ø 8 mm
Front fitting	-
Housing material	Black anodized aluminum




DATA SHEET

Weight

2 g

Dimensions (for a complete dimensional drawing please refer to the downloads section)



DOWNLOADS



921120280300.pdf (Dimensional drawing)

ACCESSORIES

POLARIZATION ANALYZER SK010PA Measurement tool for coupling into polarizationmaintaining fiber cables

RELATED PRODUCTS

POLARIZATION FILTERS 5PF

for attaching to 60FC Fiber Collimators



This is a printout of the page https://sukhamburg.com/products/details/5PF-C-400-S from 5/2/2024

CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]