

#### 5PF-C-450-S

Polarization beam splitter cube (short version)



#### **FEATURES**

Polarization filter with system mount  $\emptyset$  8 mm for attaching to <u>60FC</u> Fiber Collimators (with outer diameter  $\emptyset$  12 mm).

This filter transmits only the linear polarized component of the radiation.

- Polarization beam splitter cube with deflection of the unwanted orthogonally polarized radiation
- Polarization extinction ratio 10.000:1
- Surface deviation < λ/4</p>
- Clear aperture: 4 mm
- System mount: Ø 8 mm
- AR Coating: 450 700 nm
- Short Version without front fitting


## **TECHNICAL DATA**

5PF-C-450-S

Order Code	5PF-C-450-S
Туре	Polarizing cube beam splitter
Wavelength range	450 - 700 nm (residual reflectivity < 1.5 %)
Extinction	10.000:1
Transmission	> 95 %
AR Coating	yes
Surface deviation	< λ/4
Clear aperture	4 mm
System mount	Ø 8 mm
Front fitting	
Housing material	Black anodized aluminum

Weight 2 g

Dimensions (for a complete dimensional drawing please refer to the downloads section)



## **DOWNLOADS**



921120280300.pdf (Dimensional drawing)

# **ACCESSORIES**

POLARIZATION ANALYZER SK010PA Measurement tool for coupling into polarization-maintaining fiber cables

# **RELATED PRODUCTS**

POLARIZATION FILTERS 5PF

for attaching to 60FC Fiber Collimators



This is a printout of the page https://sukhamburg.com/products/details/5PF-C-450-S from 5/5/2024

# CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

## **LEGAL NOTICE**

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]