

5PF-P-750-S

Dichroic polarization filter (short version)



FEATURES

Polarization filter with system mount Ø 8 mm for attaching to [60FC](#) Fiber Collimators (with outer diameter Ø 12 mm).

The filter transmits only the linear polarized component of the radiation.


- Dichroic glass polarization filter. The filter is laminated to a glass substrate with an 1.5° inclined mounting in order to avoid direct back-reflections
- Polarization extinction ratio 10.000:1
- Surface deviation < $\lambda/4$
- Clear aperture: 5 mm
- System mount: Ø 8 mm
- AR Coating: 750 - 1250 nm
- Short Version without front fitting

TECHNICAL DATA

5PF-P-750-S

Order code	5PF-P-750-S
Type	Dichroic polarization filter
Wavelength range	750 - 1250 nm
Extinction	10.000:1
Transmission	> 84 - 93 %
AR coating	750 - 1250 nm (residual reflectivity < 1.5 %)
Surface deviation	< $\lambda/4$
Clear aperture	Ø 5 mm
Inclined mount	1.5°
System mount	Ø 8 mm

Front fitting	-
Housing material	Nickel silver
Weight	5 g
Dimensions (for a complete dimensional drawing please refer to the downloads section)	



DOWNLOADS



[921120280100.pdf \(Dimensional drawing\)](#)

ACCESSORIES

POLARIZATION ANALYZER SK010PA

Measurement tool for coupling into polarization-maintaining fiber cables

RELATED PRODUCTS

POLARIZATION FILTERS 5PF

for attaching to 60FC Fiber Collimators

This is a printout of the page <https://sukhamburg.com/products/details/5PF-P-750-S> from 5/4/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)