

LNC-13LT-500+91CR-639-4-H18-M60-H-6

Semi-telecentric Low Noise Micro Line Generator



FEATURES

Semi-telecentric laser line with constant line length 15mm and approx. uniform intensity distribution.

- Line length: 15 mm
- Line width: 29 μm
- Wavelength: 639 nm
- Working distance: 493 mm
- Low noise laser module (0.1 % RMS, @<1 MHz)

- Micro Line Generator for small laser line widths and high power density in the focal plane
- Low noise, low coherence laser module (typ. < 0.15 % of P_0 (RMS, Bandwidth < 1 MHz))



DESCRIPTION

The laser diode beam source type LNC-13LT-500+91CR-639-4-H18-M60-H-6 produces a semi-telecentric laser line with 15 mm line length. The intensity profile is approx. uniform in line direction. More precisely, it is Gaussian clipped by an aperture with an edge intensity of 87 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics [type H](#) for control of the laser output power. It is a low noise laser source (0.1 % RMS, @<1 MHz) with reduced coherence length and operates mode-hopping free. Due to the reduced coherence length the speckle contrast might be lowered. Please note that this effect is smaller for smaller lines and spots. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#) or manually using the potentiometer.

For this laser type the working distance is fixed. A fine-adjustment of the distance between laser and target is recommended for fine-focusing in order to achieve minimal line width.

TECHNICAL DATA

LNC-13LT-500+91CR-639-4-H18-M60-H-6

| | | |
|---------------------------|-------------------------------------|------------|
| Series | 13LT | |
| Order Code | LNC-13LT-500+91CR-639-4-H18-M60-H-6 | |
| Line profile | Constant Intensity Distribution | |
| Line type | Laser Micro Line | |
| Wavelength | 639 +10/-10 nm | |
| Laser output power | 4 mW | |
| Laser safety class | 3R | |
| Focussing range | 493-493 mm | |
| Working distance | 493 mm | |
| Line length | 15 mm | |
| Line width | 0.029 mm | |
| Rayleigh range | 2.08 mm | |
| Edge intensity | 87 % | |
| Diameter laser module | 25/28 mm | |
| Module length | 134.4 mm | |
| Installation length | 627.4 mm | |
| Cable length | 1.5 m | |
| Connector type | Lumberg SV50 IEC 61076-2-106 | |
| Supply voltage | 5 ± 0.2 V | |
| Max. current consumption | 0.25 A | |
| Working temperature | 0 - 40 °C | |
| Modulation inputs | Analog | TTL |
| Input resistance | 22 kOhm | 22 kOhm |
| Max. modulation frequency | 100 kHz | 100 kHz |
| Modulation delay ON/OFF | 2/0.3 µs | 1.5/0.1 µs |
| Rise / Fall time | 1/1 µs | 1/1 µs |
| Noise (< 1 MHz RMS) | 0.1 % | |

ACCESSORIES

| | |
|-----------|--------------------|
| 9D-12 | Screwdriver WS 1.2 |
| PS051003E | Power Supply 5 V |

RELATED PRODUCTS

LASER MODULES SERIES LNC-13LTM

- Semi-telecentric Macro Line
- Uniform intensity distribution
- Constant line length **15 mm**
- Extended depth of focus
- Low noise

LASER MODULES SERIES 13LT

- Semi-telecentric Micro Line
- Uniform intensity distribution
- Constant line length **15 mm**

LASER MODULES SERIES LNC-5LT-1

- Semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**
- Low noise

LASER MODULES SERIES LNC-5LT-2

- Semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**
- Low noise

This is a printout of the page https://sukhamburg.com/products/details/LNC-13LT-500_91CR-639-4-H18-M60-H-6 from 5/8/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)