

LNC-13M-M60+56CM-685-20-H13-T12-H-6

Low Noise Laser Micro Focus Generator with elliptical Gaussian beam profile




FEATURES

Laser spot with elliptical Gaussian beam profile.

- Spot diameter: 0.007 x 0.016 mm
- Wavelength: 685 nm
- Working distance: 54 mm
- Low noise laser module (0.1 % RMS, @<1 MHz)

- Micro Focus Generator for small spot widths and high power density in the focal plane
- Low noise, low coherence laser module (typ. < 0.15 % of P_0 (RMS, Bandwidth < 1 MHz))



DESCRIPTION

The laser diode beam source type LNC-13M-M60+56CM-685-20-H13-T12-H-6 produces an elliptical laser spot with elliptical Gaussian intensity distribution.

The laser has integrated electronics [type H](#) for control of the laser output power. It is a low noise laser source (0.1 % RMS, @<1 MHz) with reduced coherence length and operates mode-hopping free. Due to the reduced coherence length the speckle contrast might be lowered. Please note that this effect is smaller for smaller lines and spots. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that the spot diameter increases proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

LNC-13M-M60+56CM-685-20-H13-T12-H-6

Series	13M	
Order Code	LNC-13M-M60+56CM-685-20-H13-T12-H-6	
Line profile	Gaussian Intensity Distribution	
Wavelength	685 +10/-10 nm	
Laser output power	20 mW	
Laser safety class	3B	
Focussing range	40-80 mm	
Working distance	54 mm	
Spot height	0.016 mm	
Spot width	0.007 mm	
Rayleigh range	0.111 mm	
Diameter laser module	25/28 mm	
Module length	85.4 mm	
Installation length	169.4 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.25 V	
Max. current consumption	0.25 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	100 kHz	100 kHz
Modulation delay ON/OFF	2/0.3 µs	1.5/0.1 µs
Rise / Fall time	1/1 µs	1/1 µs
Noise (< 1 MHz RMS)	0.1 %	

ACCESSORIES

50HD-15	Hex key WS 1.5
9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate

13MK-25-36-10-M Mounting Console with base plate with dovetail profile

PS051003E Power Supply 5 V

RELATED PRODUCTS

**LASER MODULES
SERIES LNC-13MM**

- Macro Focus Generator
- **Circular** beam profile
- Extended depth of focus
- Low noise

**LASER MODULES
SERIES LNC-13MC**

- Micro Focus Generator
- **Rotationally symmetric**, Gaussian beam profile
- Low noise

**LASER MODULES
SERIES 13M**

- Micro Focus Generator
- Elliptical Gaussian beam profile

This is a printout of the page https://sukhamburg.com/products/details/LNC-13M-M60_56CM-685-20-H13-T12-H-6 from 6/9/2023

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)