

## LNC-13M-S000+56CM-639-10-H18-T15-H-6

Low Noise Laser Micro Focus Generator with elliptical Gaussian beam profile




### FEATURES

Laser spot with elliptical Gaussian beam profile.

- Spot diameter: 0.136 x 0.458 mm
- Wavelength: 639 nm
- Working distance: 2000 mm
- Low noise laser module (0.1 % RMS, @<1 MHz)

- Micro Focus Generator for small spot widths and high power density in the focal plane
- Low noise, low coherence laser module (typ. < 0.15 % of  $P_0$  (RMS, Bandwidth < 1 MHz))



## DESCRIPTION

The laser diode beam source type LNC-13M-S000+56CM-639-10-H18-T15-H-6 produces an elliptical laser spot with elliptical Gaussian intensity distribution.

The laser has integrated electronics [type H](#) for control of the laser output power. It is a low noise laser source (0.1 % RMS, @<1 MHz) with reduced coherence length and operates mode-hopping free. Due to the reduced coherence length the speckle contrast might be lowered. Please note that this effect is smaller for smaller lines and spots. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that the spot diameter increases proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

## TECHNICAL DATA

LNC-13M-S000+56CM-639-10-H18-T15-H-6

|                                  |                                      |            |
|----------------------------------|--------------------------------------|------------|
| <b>Series</b>                    | 13M                                  |            |
| <b>Order Code</b>                | LNC-13M-S000+56CM-639-10-H18-T15-H-6 |            |
| <b>Line profile</b>              | Gaussian Intensity Distribution      |            |
| <b>Wavelength</b>                | 639 +10/-10 nm                       |            |
| <b>Laser output power</b>        | 10 mW                                |            |
| <b>Laser safety class</b>        | 3B                                   |            |
| <b>Focussing range</b>           | 1295-inf mm                          |            |
| <b>Working distance</b>          | 2000 mm                              |            |
| <b>Spot height</b>               | 0.458 mm                             |            |
| <b>Spot width</b>                | 0.136 mm                             |            |
| <b>Rayleigh range</b>            | 45.2 mm                              |            |
| <b>Diameter laser module</b>     | 25/28 mm                             |            |
| <b>Module length</b>             | 85.4 mm                              |            |
| <b>Installation length</b>       | 2115.4 mm                            |            |
| <b>Cable length</b>              | 1.5 m                                |            |
| <b>Connector type</b>            | Lumberg SV50 IEC 61076-2-106         |            |
| <b>Supply voltage</b>            | 5 ± 0.2 V                            |            |
| <b>Max. current consumption</b>  | 0.25 A                               |            |
| <b>Working temperature</b>       | 0 - 40 °C                            |            |
| <b>Modulation inputs</b>         | Analog                               | TTL        |
| <b>Input resistance</b>          | 22 kOhm                              | 22 kOhm    |
| <b>Max. modulation frequency</b> | 100 kHz                              | 100 kHz    |
| <b>Modulation delay ON/OFF</b>   | 2/0.3 µs                             | 1.5/0.1 µs |
| <b>Rise / Fall time</b>          | 1/1 µs                               | 1/1 µs     |
| <b>Noise (&lt; 1 MHz RMS)</b>    | 0.1 %                                |            |

## DOWNLOADS



[930412000140.pdf](#)

## ACCESSORIES

|                 |  |
|-----------------|--|
| 50HD-15         | Hex key WS 1.5   |
| 9D-12           | Screwdriver WS 1.2                                     |
| 13MK-25-36-10-F | Mounting Console with flat base plate                  |
| 13MK-25-36-10-M | Mounting Console with base plate with dovetail profile |
| PS051003E       | Power Supply 5 V                                       |

## RELATED PRODUCTS

### LASER MODULES SERIES LNC-13MM

- Macro Focus Generator
- **Circular** beam profile
- Extended depth of focus
- Low noise

### LASER MODULES SERIES LNC-13MC

- Micro Focus Generator
- **Rotationally symmetric**, Gaussian beam profile
- Low noise

### LASER MODULES SERIES 13M

- Micro Focus Generator
- Elliptical Gaussian beam profile

This is a printout of the page [https://sukhamburg.com/products/details/LNC-13M-S000\\_56CM-639-10-H18-T15-H-6](https://sukhamburg.com/products/details/LNC-13M-S000_56CM-639-10-H18-T15-H-6) from 9/23/2023

## CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

[info@sukhamburg.de](mailto:info@sukhamburg.de)

[www.sukhamburg.com](http://www.sukhamburg.com)

## LEGAL NOTICE

**Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.**

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)