

### LNC-5LM15-S000+56CM-639-9-H18-A8-H-6

Low Noise Micro Line Generator with a fan angle



#### **FEATURES**

Laser line with a fan angle and Gaussian intensity distribution.

Line length: 266 mm
Line width: 430 μm
Wavelength: 639 nm

Working distance: 1000 mm

Low noise laser module (0.1 % RMS, @<1 MHz)</li>

- Micro Line Generator for small laser line widths and high power density in the focal plane
- Low noise, low coherence laser module (typ. < 0.15 % of P<sub>0</sub> (RMS, Bandwidth < 1 MHz))</li>





## **DESCRIPTION**

The laser diode beam source type LNC-5LM15-S000+56CM-639-9-H18-A8-H-6 has a fan angle of 15°.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 38 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics <u>type H</u> for control of the laser output power. It is a low noise laser source (0.1 % RMS,@<1 MHz) with reduced coherence length and operates mode-hopping free. Due to the reduced coherence length the speckle contrast might be lowered. Please note that this effect is smaller for smaller lines and spots. The output power can be controlled using the  $\underline{\text{modulation input ports (TTL and analog)}}$  or manually using the potentiometer.



The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance.

A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

# **TECHNICAL DATA**

LNC-5LM15-S000+56CM-639-9-H18-A8-H-6

Series		5LM	
Order Code	LNC-5LM15-S000+56CM-639-9-H18-A8-H-6		
Line profile	Gaussian Intensity Distribution		
Line type	Laser Micro Line		
Wavelength	639 +10/-10 nm		
Laser output power	9 mW		
Laser safety class	3B		
Fan angle α	15 deg		
Focussing range	425-inf mm		
Working distance	1000 mm		
Line length	266 mm		
Line width	0.43 mm		
Rayleigh range	454 mm		
Edge intensity	38 %		
Diameter laser module	25/28 mm		
Module length	82.6 mm		
Installation length	1112.6 mm		
Cable length	1.5 m		
Connector type	Lumberg SV50 IEC 61076-2-106		
Supply voltage	5 ± 0.2 V		
Max. current consumption	0.25 A		
Working temperature		0 - 40 °C	
Modulation inputs	Analog	TTL	
Input resistance	22 kOhm	22 kOhm	
Max. modulation frequency	100 kHz	100 kHz	
Modulation delay ON/OFF	2/0.3 μs	1.5/0.1 μs	
Rise / Fall time	1/1 μs	1/1 μs	



Noise (< 1 MHZ RMS) 0.1%

# **ACCESSORIES**

50HD-15 Hex key WS 1.5

9D-12 Screwdriver WS 1.2

13MK-25-36-10-F Mounting Console with flat base plate

13MK-25-36-10-M Mounting Console with base plate with dovetail

profile

PS051003E Power Supply 5 V

# **RELATED PRODUCTS**

LASER MODULES Macro Line, small fan angle

**SERIES LNC-5LMM** Gaussian intensity distribution

Extended depth of focus

Low Noise

LASER MODULES Micro Line, small fan angle

**SERIES 5LM** Gaussian intensity distribution

**LASER MODULES** Micro Line, small fan angle **SERIES LNC-13LN** 

Uniform intensity distribution

Thin lines Low noise

LASER MODULES ■ Micro Line, large fan angle

**SERIES LNC-5LP** Gaussian intensity distribution

Low noise



This is a printout of the page <a href="https://sukhamburg.com/products/details/LNC-5LM15-S000\_56CM-639-9-H18-A8-H-6">https://sukhamburg.com/products/details/LNC-5LM15-S000\_56CM-639-9-H18-A8-H-6</a> from 4/25/2024

#### CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

### **LEGAL NOTICE**

#### Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]