

LNC-5LM15-S150+56CM-640-14-H22-A8-H-6

Low Noise Micro Line Generator with a fan angle



FEATURES

Laser line with a fan angle and Gaussian intensity distribution.

- Line length: 39.7 mm
- Line width: 57 μm
- Wavelength: 640 nm
- Working distance: 143 mm
- Low noise laser module (0.1 % RMS, @<1 MHz)

- Micro Line Generator for small laser line widths and high power density in the focal plane
- Low noise, low coherence laser module (typ. < 0.15 % of P_0 (RMS, Bandwidth < 1 MHz))



DESCRIPTION

The laser diode beam source type LNC-5LM15-S150+56CM-640-14-H22-A8-H-6 has a fan angle of 15°.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 13 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics [type H](#) for control of the laser output power. It is a low noise laser source (0.1 % RMS, @<1 MHz) with reduced coherence length and operates mode-hopping free. Due to the reduced coherence length the speckle contrast might be lowered. Please note that this effect is smaller for smaller lines and spots. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#) or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance.

A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

LNC-5LM15-S150+56CM-640-14-H22-A8-H-6

Series	5LM	
Order Code	LNC-5LM15-S150+56CM-640-14-H22-A8-H-6	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Micro Line	
Wavelength	640 +5/-5 nm	
Laser output power	14 mW	
Laser safety class	3B	
Fan angle α	15 deg	
Focussing range	120-255 mm	
Working distance	143 mm	
Line length	39.7 mm	
Line width	0.057 mm	
Rayleigh range	8.1 mm	
Edge intensity	13 %	
Diameter laser module	25/28 mm	
Module length	86.8 mm	
Installation length	259.8 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 \pm 0.2 V	
Max. current consumption	0.25 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	100 kHz	100 kHz
Modulation delay ON/OFF	2/0.3 μ s	1.5/0.1 μ s
Rise / Fall time	1/1 μ s	1/1 μ s

Noise (< 1 MHz RMS)

0.1 %

ACCESSORIES

50HD-15	Hex key WS 1.5
9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS051003E	Power Supply 5 V

RELATED PRODUCTS

LASER MODULES SERIES LNC-5LMM	▪ Macro Line, small fan angle
	▪ Gaussian intensity distribution
	▪ Extended depth of focus
	▪ Low Noise

LASER MODULES SERIES 5LM	▪ Micro Line, small fan angle
	▪ Gaussian intensity distribution

LASER MODULES SERIES LNC-13LN	▪ Micro Line, small fan angle
	▪ Uniform intensity distribution
	▪ Thin lines
	▪ Low noise

LASER MODULES SERIES LNC-5LP	▪ Micro Line, large fan angle
	▪ Gaussian intensity distribution
	▪ Low noise

This is a printout of the page https://sukhamburg.com/products/details/LNC-5LM15-S150_56CM-640-14-H22-A8-H-6 from 5/3/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)