

LNC-5LM15-S88+56CM-685-19-H13-A8-H-6

Low Noise Micro Line Generator with a fan angle



FEATURES

Laser line with a fan angle and Gaussian intensity distribution.

Line length: 21.9 mm
Line width: 34 μm
Wavelength: 685 nm
Working distance: 78 mm

Low noise laser module (0.1 % RMS, @<1 MHz)

- Micro Line Generator for small laser line widths and high power density in the focal plane
- Low noise, low coherence laser module (typ. < 0.15 % of P₀ (RMS, Bandwidth < 1 MHz))





DESCRIPTION

The laser diode beam source type LNC-5LM15-S88+56CM-685-19-H13-A8-H-6 has a fan angle of 15°.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 14 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics <u>type H</u> for control of the laser output power. It is a low noise laser source (0.1 % RMS,@<1 MHz) with reduced coherence length and operates mode-hopping free. Due to the reduced coherence length the speckle contrast might be lowered. Please note that this effect is smaller for smaller lines and spots. The output power can be controlled using the $\underline{\text{modulation input ports (TTL and analog)}}$ or manually using the potentiometer.



The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance.

A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

LNC-5LM15-S88+56CM-685-19-H13-A8-H-6

Max. modulation frequency100 kHz100 kHzModulation delay ON/OFF2/0.3 μs1.5/0.1 μs	Series		5LM	
Line type Laser Micro Line Wavelength 685 +10/-10 nm Laser output power 19 mW Laser safety class 3B Fan angle α 15 deg Focussing range 65-120 mm Working distance 78 mm Line length 21.9 mm Line width 0.034 mm Rayleigh range 2.68 mm Edge intensity 14 % Diameter laser module 25/28 mm Module length 86.8 mm Installation length 194.8 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.25 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation delay ON/OFF 2/0.3 μs 1.5/0.1 μs	Order Code	LNC-5LM15-S88+56CM-685-19-H13-A8-H-6		
Wavelength 685 +10/-10 nm Laser output power 19 mW Laser safety class 3B Fan angle α 15 deg Focussing range 65-120 mm Working distance 78 mm Line length 21.9 mm Line width 0.034 mm Rayleigh range 2.68 mm Edge intensity 14 % Diameter laser module 25/28 mm Module length 86.8 mm Installation length 194.8 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.25 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz Modulation delay ON/OFF 2/0.3 μs 1.5/0.1 μs	Line profile	Gaussian Intensity Distribution		
Laser output power 19 mW Laser safety class 3B Fan angle α 15 deg Focussing range 65-120 mm Working distance 78 mm Line length 21.9 mm Line width 0.034 mm Rayleigh range 2.68 mm Edge intensity 14 % Diameter laser module 25/28 mm Module length 86.8 mm Installation length 194.8 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.25 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz Modulation delay ON/OFF 2/0.3 μs 1.5/0.1 μs	Line type	Laser Micro Line		
Laser safety class3BFan angle α15 degFocussing range65-120 mmWorking distance78 mmLine length21.9 mmLine width0.034 mmRayleigh range2.68 mmEdge intensity14 %Diameter laser module25/28 mmModule length86.8 mmInstallation length194.8 mmCable length1.5 mConnector typeLumberg SV50 IEC 61076-2-106Supply voltage $5 \pm 0.25 \text{ V}$ Max. current consumption0.25 AWorking temperature $0 - 40 ^{\circ}\text{C}$ Modulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHzModulation delay ON/OFF2/0.3 μs1.5/0.1 μs	Wavelength	685 +10/-10 nm		
Fan angle α 15 deg Focussing range 65-120 mm Working distance 78 mm Line length 21.9 mm Line width 0.034 mm Rayleigh range 2.68 mm Edge intensity 14 % Diameter laser module 25/28 mm Module length 86.8 mm Installation length 194.8 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.25 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz Modulation delay ON/OFF 2/0.3 μs 1.5/0.1 μs	Laser output power	19 mW		
Focussing range 65-120 mm Working distance 78 mm Line length 21.9 mm Line width 0.034 mm Rayleigh range 2.68 mm Edge intensity 14 % Diameter laser module 25/28 mm Module length 86.8 mm Installation length 194.8 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.25 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz Modulation delay ON/OFF 2/0.3 μs 1.5/0.1 μs	Laser safety class	3B		
Working distance 78 mm Line length 21.9 mm Line width 0.034 mm Rayleigh range 2.68 mm Edge intensity 14 % Diameter laser module 25/28 mm Module length 86.8 mm Installation length 194.8 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.25 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz Modulation delay ON/OFF 2/0.3 μs 1.5/0.1 μs	Fan angle α	15 deg		
Line length 21.9 mm Line width 0.034 mm Rayleigh range 2.68 mm Edge intensity 14 % Diameter laser module 25/28 mm Module length 86.8 mm Installation length 194.8 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.25 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz Modulation delay ON/OFF 2/0.3 μs 1.5/0.1 μs	Focussing range	65-120 mm		
Line width 0.034 mm Rayleigh range 2.68 mm Edge intensity 14 % Diameter laser module 25/28 mm Module length 86.8 mm Installation length 194.8 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.25 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz Modulation delay ON/OFF 2/0.3 μs 1.5/0.1 μs	Working distance	78 mm		
Rayleigh range2.68 mmEdge intensity14 %Diameter laser module25/28 mmModule length86.8 mmInstallation length194.8 mmCable length1.5 mConnector typeLumberg SV50 IEC 61076-2-106Supply voltage5 ± 0.25 VMax. current consumption0.25 AWorking temperature0 - 40 °CModulation inputsAnalogTTLInput resistance22 kOhmMax. modulation frequency100 kHzModulation delay ON/OFF2/0.3 μs1.5/0.1 μs	Line length	21.9 mm		
Edge intensity14 %Diameter laser module25/28 mmModule length86.8 mmInstallation length194.8 mmCable length1.5 mConnector typeLumberg SV50 IEC 61076-2-106Supply voltage5 ± 0.25 VMax. current consumption0.25 AWorking temperature0 - 40 °CModulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHzModulation delay ON/OFF2/0.3 μs1.5/0.1 μs	Line width	0.034 mm		
Diameter laser module 25/28 mm Module length 86.8 mm Installation length 194.8 mm Cable length 1.5 m Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.25 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm 22 kOhm Max. modulation frequency 100 kHz 100 kHz Modulation delay ON/OFF 2/0.3 μs 1.5/0.1 μs	Rayleigh range	2.68 mm		
Module length 86.8mm Installation length 194.8mm Cable length 1.5m Connector typeLumberg SV50 IEC 61076-2-106Supply voltage $5 \pm 0.25 \text{V}$ Max. current consumption 0.25A Working temperature $0 - 40 ^{\circ}\text{C}$ Modulation inputsAnalogTTLInput resistance 22kOhm 22kOhm Max. modulation frequency 100kHz 100kHz Modulation delay ON/OFF $2/0.3 \mu \text{s}$ $1.5/0.1 \mu \text{s}$	Edge intensity	14%		
Installation length Cable length Connector type Lumberg SV50 IEC 61076-2-106 Supply voltage 5 ± 0.25 V Max. current consumption 0.25 A Working temperature 0 - 40 °C Modulation inputs Analog TTL Input resistance 22 kOhm Max. modulation frequency 100 kHz Modulation delay ON/OFF 2/0.3 µs 1.5/0.1 µs	Diameter laser module	25/28 mm		
Cable length1.5 mConnector typeLumberg SV50 IEC 61076-2-106Supply voltage5 ± 0.25 VMax. current consumption0.25 AWorking temperature0 - 40 °CModulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHzModulation delay ON/OFF2/0.3 μs1.5/0.1 μs	Module length	86.8 mm		
Connector typeLumberg SV50 IEC 61076-2-106Supply voltage5 ± 0.25 VMax. current consumption0.25 AWorking temperature0 - 40 °CModulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHzModulation delay ON/OFF2/0.3 μs1.5/0.1 μs	Installation length	194.8 mm		
	Cable length	1.5 m		
Max. current consumption0.25 AWorking temperature0 - 40 °CModulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHzModulation delay ON/OFF2/0.3 μs1.5/0.1 μs	Connector type	Lumberg SV50 IEC 61076-2-106		
Working temperature0 - 40 °CModulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHzModulation delay ON/OFF2/0.3 μs1.5/0.1 μs	Supply voltage	5 ± 0.25 V		
Modulation inputsAnalogTTLInput resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHzModulation delay ON/OFF2/0.3 μs1.5/0.1 μs	Max. current consumption	0.25 A		
Input resistance22 kOhm22 kOhmMax. modulation frequency100 kHz100 kHzModulation delay ON/OFF2/0.3 μs1.5/0.1 μs	Working temperature		0 - 40 °C	
Max. modulation frequency100 kHz100 kHzModulation delay ON/OFF2/0.3 μs1.5/0.1 μs	Modulation inputs	Analog	TTL	
Modulation delay ON/OFF 2/0.3 μs 1.5/0.1 μs	Input resistance	22 kOhm	22 kOhm	
	Max. modulation frequency	100 kHz	100 kHz	
Pice / Fall time	Modulation delay ON/OFF	2/0.3 μs	1.5/0.1 μs	
1/1 μ5 1/1 μ5	Rise / Fall time	1/1 μs	1/1 μs	



Noise (< 1 MHZ RMS) 0.1%

ACCESSORIES

50HD-15 Hex key WS 1.5

9D-12 Screwdriver WS 1.2

13MK-25-36-10-F Mounting Console with flat base plate

13MK-25-36-10-M Mounting Console with base plate with dovetail

profile

PS051003E Power Supply 5 V

RELATED PRODUCTS

LASER MODULES Macro Line, small fan angle

SERIES LNC-5LMM Gaussian intensity distribution

Extended depth of focus

Low Noise

LASER MODULES Micro Line, small fan angle

SERIES 5LM Gaussian intensity distribution

LASER MODULES Micro Line, small fan angle **SERIES LNC-13LN**

Uniform intensity distribution

Thin lines Low noise

LASER MODULES ■ Micro Line, large fan angle

SERIES LNC-5LP Gaussian intensity distribution

Low noise



This is a printout of the page https://sukhamburg.com/products/details/LNC-5LM15-S88_56CM-685-19-H13-A8-H-6 from 4/26/2024

CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]