

LNC-5LM8-S000+56CM-520-13-O11-A7.5-HP-4

Low Noise Micro Line Generator with a fan angle



FEATURES

Laser line with a fan angle and Gaussian intensity distribution.

- Line length: 140 mm
- Line width: 481 μm
- Wavelength: 520 nm
- Working distance: 1000 mm
- Low noise laser module (0.1 % RMS, @<1 MHz)

- Micro Line Generator for small laser line widths and high power density in the focal plane
- Low noise, low coherence laser module (typ. < 0.15 % of P_0 (RMS, Bandwidth < 1 MHz))



DESCRIPTION

The laser diode beam source type LNC-5LM8-S000+56CM-520-13-O11-A7.5-HP-4 has a fan angle of 8°.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 18 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics [type HP](#) with micro-controller for control of the laser output power. It is a low noise laser source (0.1 % RMS, @<1 MHz) with reduced coherence length and operates mode-hopping free. Due to the reduced coherence length the speckle contrast might be lowered. Please note that this effect is smaller for smaller lines and spots. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance.

A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

LNC-5LM8-S000+56CM-520-13-O11-A7.5-HP-4

Series	5LM	
Order Code	LNC-5LM8-S000+56CM-520-13-O11-A7.5-HP-4	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Micro Line	
Wavelength	520 +10/-5 nm	
Laser output power	13 mW	
Laser safety class	3B	
Fan angle α	8 deg	
Focussing range	425-inf mm	
Working distance	1000 mm	
Line length	140 mm	
Line width	0.481 mm	
Rayleigh range	699 mm	
Edge intensity	18 %	
Diameter laser module	25/28 mm	
Module length	82.6 mm	
Installation length	1112.6 mm	
Cable length	1.5 m	
Connector type	Lumberg SV40 IEC 61076-2-106	
Supply voltage	12 \pm 0.5 V	
Max. current consumption	0.3 A	
Working temperature	15 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	9 kOhm	9 kOhm
Max. modulation frequency	0.001 kHz	300 kHz
Modulation delay ON/OFF	2000/500 μ s	0.5/0.2 μ s
Rise / Fall time	200000/200000 μ s	0.8/0.3 μ s

Noise (< 1 MHz RMS)

0.1 %

ACCESSORIES

50HD-15	Hex key WS 1.5
9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS120516E	Power Supply 12 V

RELATED PRODUCTS

LASER MODULES SERIES LNC-5LMM	<ul style="list-style-type: none">▪ Macro Line, small fan angle▪ Gaussian intensity distribution▪ Extended depth of focus▪ Low Noise
----------------------------------	--

LASER MODULES SERIES 5LM	<ul style="list-style-type: none">▪ Micro Line, small fan angle▪ Gaussian intensity distribution
-----------------------------	--

LASER MODULES SERIES LNC-13LN	<ul style="list-style-type: none">▪ Micro Line, small fan angle▪ Uniform intensity distribution▪ Thin lines▪ Low noise
----------------------------------	--

LASER MODULES SERIES LNC-5LP	<ul style="list-style-type: none">▪ Micro Line, large fan angle▪ Gaussian intensity distribution▪ Low noise
---------------------------------	--

This is a printout of the page https://sukhamburg.com/products/details/LNC-5LM8-S000_56CM-520-13-O11-A7_5-HP-4 from 5/4/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)