

# LNC-5LM8-S325+56CM-520-13-O11-A7.5-HP-4

Low Noise Micro Line Generator with a fan angle



#### **FEATURES**

Laser line with a fan angle and Gaussian intensity distribution.

Line length: 47.5 mm
Line width: 156 μm
Wavelength: 520 nm
Working distance: 313 mm

Low noise laser module (0.1 % RMS, @<1 MHz)</li>

- Micro Line Generator for small laser line widths and high power density in the focal plane
- Low noise, low coherence laser module (typ. < 0.15 % of P<sub>0</sub> (RMS, Bandwidth < 1 MHz))</li>





## **DESCRIPTION**

The laser diode beam source type LNC-5LM8-S325+56CM-520-13-O11-A7.5-HP-4 has a fan angle of 8°.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 18 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics <u>type HP</u> with micro-controller for control of the laser output power. It is a low noise laser source (0.1 % RMS,@<1 MHz) with reduced coherence length and operates mode-hopping free. Due to the reduced coherence length the speckle contrast might be lowered. Please note that this effect is smaller for smaller lines and spots. The output power can be controlled using the <u>modulation input ports (TTL and analog)</u> or manually using the potentiometer.



The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance.

A fine-adjustment of the distance between laser and target is recommended for finefocusing.

# **TECHNICAL DATA**

LNC-5LM8-S325+56CM-520-13-O11-A7.5-HP-4

Series	5LM	
Order Code	LNC-5LM8-S325+56CM-520-13-O11-A7.5-HP-4	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Micro Line	
Wavelength	520 +10/-5 nm	
Laser output power	13 mW	
Laser safety class	3B	
Fan angle α	8 deg	
Focussing range	255-425 mm	
Working distance	313 mm	
Line length	47.5 mm	
Line width	0.156 mm	
Rayleigh range	73.8 mm	
Edge intensity	18 %	
Diameter laser module	25/28 mm	
Module length	86.8 mm	
Installation length	429.8 mm	
Cable length	1.5 m	
Connector type	Lumberg SV40 IEC 61076-2-106	
Supply voltage	12 ± 0.5 V	
Max. current consumption	0.3A	
Working temperature	15 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	9 kOhm	9 kOhm
Max. modulation frequency	0.001 kHz	300 kHz
Modulation delay ON/OFF	2000/500 μs	0.5/0.2 μs
Rise / Fall time	200000/200000 μs	0.8/0.3 μs



Noise (< 1 MHZ RMS) 0.1%

## **ACCESSORIES**

50HD-15 Hex key WS 1.5

9D-12 Screwdriver WS 1.2

13MK-25-36-10-F Mounting Console with flat base plate

13MK-25-36-10-M Mounting Console with base plate with dovetail

profile

PS120516E Power Supply 12 V

# RELATED PRODUCTS

**LASER MODULES** Macro Line, small fan angle **SERIES LNC-5LMM** 

Gaussian intensity distribution

Extended depth of focus

Low Noise

LASER MODULES Micro Line, small fan angle **SERIES 5LM** 

Gaussian intensity distribution

LASER MODULES • Micro Line, small fan angle

**SERIES LNC-13LN** Uniform intensity distribution

> Thin lines Low noise

LASER MODULES Micro Line, large fan angle **SERIES LNC-5LP** 

Gaussian intensity distribution

Low noise



This is a printout of the page <a href="https://sukhamburg.com/products/details/LNC-5LM8-S325">https://sukhamburg.com/products/details/LNC-5LM8-S325</a> 56CM-520-13-O11-A7 5-HP-4 from 5/6/2024

## CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

## **LEGAL NOTICE**

### Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]