## LNC-5LM8-S88+56CM-405-36-X15-A7.5-HP-4


Low Noise Micro Line Generator with a fan angle



#### FEATURES

Laser line with a fan angle and Gaussian intensity distribution.

- Line length: 12 mm
- Line width: 23 μm
- Wavelength: 405 nm
- Working distance: 78 mm
- Low noise laser module (0.1 % RMS, @<1 MHz)</li>
- Micro Line Generator for small laser line widths and high power density in the focal plane
- Low noise, low coherence laser module (typ. < 0.15 % of P<sub>0</sub> (RMS, Bandwidth < 1 MHz))</li>



# DESCRIPTION

The laser diode beam source type LNC-5LM8-S88+56CM-405-36-X15-A7.5-HP-4 has a fan angle of 8°.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 10 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics <u>type HP</u> with micro-controller for control of the laser output power. It is a low noise laser source (0.1 % RMS,@<1 MHz) with reduced coherence length and operates mode-hopping free. Due to the reduced coherence length the speckle contrast might be lowered. Please note that this effect is smaller for smaller lines and spots. The output power can be controlled using the <u>modulation input</u> ports (<u>TTL and analog</u>) or manually using the potentiometer.



The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance.

A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

## **TECHNICAL DATA**

LNC-5LM8-S88+56CM-405-36-X15-A7.5-HP-4

Series		5LM
Order Code	LNC-5LM8-S88+56CM-405-36-X15-A7.5-HP-4	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Micro Line	
Wavelength	405 +5/-5 nm	
Laser output power	36 mW	
Laser safety class	3В	
Fan angle α	8 deg	
Focussing range65-120 mm		
Working distance78 mm		
Line length	e length 12 mm	
Line width	0.023 mm	
Rayleigh range	2.01 mm	
Edge intensity 10 %		
Diameter laser module	25/28 mm	
Module length	86.8 mm	
Installation length	194.8 mm	
Cable length		1.5 m
Connector type	Lumberg SV40 IEC 61076-2-106	
Supply voltage	12 ± 0.5 V	
Max. current consumption	0.3 A	
Working temperature	15 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	9 kOhm	9 kOhm
Max. modulation frequency	0.001 kHz	300 kHz
Modulation delay ON/OFF	2000/500 µs	0.5/0.2 μs
Rise / Fall time	200000/200000 µs	0.8/0.3 µs



Noise (< 1 MHZ RMS)

0.1%

# ACCESSORIES

50HD-15	Hex key WS 1.5
9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS120516E	Power Supply 12 V

# **RELATED PRODUCTS**

LASER MODULES SERIES LNC-5LMM	<ul> <li>Macro Line, small fan angle</li> <li>Gaussian intensity distribution</li> <li>Extended depth of focus</li> <li>Low Noise</li> </ul>
LASER MODULES SERIES 5LM	<ul> <li>Micro Line, small fan angle</li> <li>Gaussian intensity distribution</li> </ul>
LASER MODULES SERIES LNC-13LN	<ul> <li>Micro Line, small fan angle</li> <li>Uniform intensity distribution</li> <li>Thin lines</li> <li>Low noise</li> </ul>
LASER MODULES SERIES LNC-5LP	<ul> <li>Micro Line, large fan angle</li> <li>Gaussian intensity distribution</li> <li>Low noise</li> </ul>

# **DATA SHEET**

This is a printout of the page <u>https://sukhamburg.com/products/details/LNC-5LM8-S88\_56CM-405-36-X15-A7\_5-HP-4</u> from 4/23/2024

# CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

# **LEGAL NOTICE**

#### Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]

