


LNC-5LMM15-S325-1+56CM-640-9-H22-A8-H-6

Low Noise Macro Line Generator with a fan angle



FEATURES

Laser line with a fan angle, Gaussian intensity distribution and extended depth of focus.

Line length: 86.9 mm
Line width: 301 µm
Wavelength: 640 nm
Working distance: 308 mm
Depth of focus: 301 mm

Low noise laser module (0.1 % RMS, @<1 MHz)

- Macro Line Generator for extended depth of focus
- Low noise, low coherence laser module (typ. < 0.15 % of P_o (RMS, Bandwidth < 1 MHz))





DESCRIPTION

The laser diode beam source type LNC-5LMM15-S325-1+56CM-640-9-H22-A8-H-6 has a fan angle of 15° and an extended depth of focus.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 13 %. The line width is constant along the laser line. Across the laser line the intensity distribution is approx. Gaussian.



The laser has integrated electronics <u>type H</u> for control of the laser output power. It is a low noise laser source (0.1 % RMS,@<1 MHz) with reduced coherence length and operates mode-hopping free. Due to the reduced coherence length the speckle contrast might be lowered. Please note that this effect is smaller for smaller lines and spots. The output power can be controlled using the <u>modulation input ports (TTL and analog)</u> or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

LNC-5LMM15-S325-1+56CM-640-9-H22-A8-H-6

Series	5LMM	
Order Code	LNC-5LMM15-S325-1+56CM-640-9-H22-A8-H-6	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Macro Line	
Wavelength	640 +5/-5 nm	
Laser output power	9 mW	
Laser safety class	3B	
Fan angle α	15 deg	
Focussing range	250-450 mm	
Working distance	308 mm	
Line length	86.9 mm	
Line width	0.301 mm	
Depth of focus	301 mm	
Edge intensity	13 %	
Diameter laser module	25/28 mm	
Module length	88 mm	
Installation length	426 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.2 V	
Max. current consumption	0.25 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm



Max. modulation frequency	100 kHz	100 kHz
Modulation delay ON/OFF	2/0.3 μs	1.5/0.1 μs
Rise / Fall time	1/1 µs	1/1 μs
Noise (< 1 MHZ RMS)		0.1 %

ACCESSORIES

50HD-15 Hex key WS 1.5

9D-12 Screwdriver WS 1.2

13MK-25-36-10-F Mounting Console with flat base plate

13MK-25-36-10-M Mounting Console with base plate with dovetail

profile

PS051003E Power Supply 5 V

RELATED PRODUCTS

SERIES 5LMM

SERIES LNC-5LPM

LASER MODULES Macro Line, small fan angle **SERIES LNC-5LMM**

Gaussian intensity distribution

Extended depth of focus

Low Noise

LASER MODULES Macro Line, small fan angle

Gaussian intensity distribution

Extended depth of focus

LASER MODULES Macro Line Generator, small fan angle

SERIES LNC-13LNM Uniform intensity distribution

Extended depth of focus

Low noise

LASER MODULES Macro Line, large fan angle

Gaussian intensity distribution

Extended depth of focus

Low noise



This is a printout of the page https://sukhamburg.com/products/details/LNC-5LMM15-S325-1_56CM-640-9-H22-A8-H-6 from 4/26/2024

CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]