#### LNC-5LP40-S000+56CR-640-13-H22-A8-H-6


Low Noise Micro Line Generator with a large fan angle



#### FEATURES

Laser line with a large fan angle and Gaussian intensity distribution.

- Line length: 720 mm
- Line width: 383 μm
- Wavelength: 640 nm
- Working distance: 1000 mm
- Low noise laser module (0.1 % RMS, @<1 MHz)</li>
- Micro Line Generator for small laser line widths and high power density in the focal plane
- Low noise, low coherence laser module (typ. < 0.15 % of P<sub>0</sub> (RMS, Bandwidth < 1 MHz))</li>



## DESCRIPTION

The laser diode beam source type LNC-5LP40-S000+56CR-640-13-H22-A8-H-6 has a fan angle of 40°.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 13 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics <u>type H</u> for control of the laser output power. It is a low noise laser source (0.1 % RMS,@<1 MHz) with reduced coherence length and operates mode-hopping free. Due to the reduced coherence length the speckle contrast might be lowered. Please note that this effect is smaller for smaller lines and spots. The output power can be controlled using the <u>modulation input ports (TTL and analog)</u> or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

# **TECHNICAL DATA**

LNC-5LP40-S000+56CR-640-13-H22-A8-H-6

Series		5LP
Order Code	LNC-5LP40-S000+56CR-640-13-H22-A8-H-6	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Micro Line	
Wavelength	640 +5/-5 nm	
Laser output power	13 mW	
Laser safety class		3B
Fan angle $\alpha$	40 deg	
Focussing range	430-inf mm	
Vorking distance 1000 mm		
Line length		720 mm
Line width	0.383 mm	
Rayleigh range	360 mm	
Edge intensity	13 %	
Diameter laser module	25/28 mm	
Module length	102.6 mm	
Installation length	1102.6 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.2 V	
Max. current consumption	0.25 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	100 kHz	100 kHz
Modulation delay ON/OFF	2/0.3 µs	1.5/0.1 μs
Rise / Fall time	1/1 µs	1/1 µs



Noise (< 1 MHZ RMS)

0.1%

# ACCESSORIES

50HD-15	Hex key WS 1.5
9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13МК-25-36-10-М	Mounting Console with base plate with dovetail profile
PS051003E	Power Supply 5 V

# **RELATED PRODUCTS**

LASER MODULES SERIES LNC-5LPM	<ul> <li>Macro Line, large fan angle</li> <li>Gaussian intensity distribution</li> <li>Extended depth of focus</li> <li>Low noise</li> </ul>
LASER MODULES SERIES 5LP	<ul> <li>Micro Line, large fan angle</li> <li>Gaussian intensity distribution</li> </ul>
LASER MODULES SERIES LNC-13LN	<ul> <li>Micro Line, small fan angle</li> <li>Uniform intensity distribution</li> <li>Thin lines</li> <li>Low noise</li> </ul>
LASER MODULES SERIES LNC-5LM	<ul> <li>Micro Line, small fan angle</li> <li>Gaussian intensity distribution</li> <li>Low noise</li> </ul>



### **DATA SHEET**

This is a printout of the page <u>https://sukhamburg.com/products/details/LNC-5LP40-S000\_56CR-640-13-H22-A8-H-6</u> from 5/7/2024

# CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

# **LEGAL NOTICE**

#### Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]

