

LNC-5LP60-S325+56CM-640-13-H22-A8-H-6

Low Noise Micro Line Generator with a large fan angle



FEATURES

Laser line with a large fan angle and Gaussian intensity distribution.

Line length: 375 mm
Line width: 124 μm
Wavelength: 640 nm
Working distance: 317 mm

Low noise laser module (0.1 % RMS, @<1 MHz)

- Micro Line Generator for small laser line widths and high power density in the focal plane
- Low noise, low coherence laser module (typ. < 0.15 % of P₀ (RMS, Bandwidth < 1 MHz))





DESCRIPTION

The laser diode beam source type LNC-5LP60-S325+56CM-640-13-H22-A8-H-6 has a fan angle of 62°.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 13 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics $\underline{type\ H}$ for control of the laser output power. It is a low noise laser source (0.1 % RMS,@<1 MHz) with reduced coherence length and operates mode-hopping free. Due to the reduced coherence length the speckle contrast might be lowered. Please note that this effect is smaller for smaller lines and spots. The output power can be controlled using the $\underline{modulation\ input\ ports\ (TTL\ and\ analog)}$ or manually using the potentiometer.



The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

LNC-5LP60-S325+56CM-640-13-H22-A8-H-6

Series 5LP			
Order Code	LNC-5LP60-S325+56CM-640-13-H22-A8-H-6		
Line profile	Gaussian Intensity Distribution		
Line type	Laser Micro Line		
Wavelength	640 +5/-5 nm		
Laser output power	13 mW		
Laser safety class	3B		
Fan angle α	62 deg		
Focussing range	ssing range 260-430 mm		
Working distance	317 mm		
Line length	375 mm		
Line width	0.124 mm		
Rayleigh range	38 mm		
Edge intensity	13 %		
Diameter laser module	25/28 mm		
Module length	95.6 mm		
Installation length	442.6 mm		
Cable length	1.5 m		
Connector type	Lumberg SV50 II	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.2 V		
Max. current consumption	0.25 A		
Working temperature		0 - 40 °C	
Modulation inputs	Analog	TTL	
Input resistance	22 kOhm	22 kOhm	
Max. modulation frequency	100 kHz	100 kHz	
Modulation delay ON/OFF	2/0.3 μs	1.5/0.1 μs	
Rise / Fall time	1/1 μs	1/1 µs	



Noise (< 1 MHZ RMS) 0.1%

ACCESSORIES

50HD-15 Hex key WS 1.5

9D-12 Screwdriver WS 1.2

13MK-25-36-10-F Mounting Console with flat base plate

13MK-25-36-10-M Mounting Console with base plate with dovetail

profile

PS051003E Power Supply 5 V

RELATED PRODUCTS

LASER MODULES Macro Line, large fan angle

SERIES LNC-5LPM Gaussian intensity distribution

Extended depth of focus

Low noise

LASER MODULES Micro Line, large fan angle

SERIES 5LP Gaussian intensity distribution

LASER MODULES Micro Line, small fan angle **SERIES LNC-13LN**

 Uniform intensity distribution Thin lines

Low noise

LASER MODULES Micro Line, small fan angle

SERIES LNC-5LM Gaussian intensity distribution

Low noise



This is a printout of the page https://sukhamburg.com/products/details/LNC-5LP60-S325_56CM-640-13-H22-A8-H-6 from 4/24/2024

CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]