

## LNC-5LP60-S325+56CR-520-13-O11-A7.5-HP-4

Low Noise Micro Line Generator with a large fan angle



### FEATURES

Laser line with a large fan angle and Gaussian intensity distribution.

- Line length: 375 mm
- Line width: 156  $\mu\text{m}$
- Wavelength: 520 nm
- Working distance: 317 mm
- Low noise laser module (0.1 % RMS, @<1 MHz)

- Micro Line Generator for small laser line widths and high power density in the focal plane
- Low noise, low coherence laser module (typ. < 0.15 % of  $P_0$  (RMS, Bandwidth < 1 MHz))



## DESCRIPTION

The laser diode beam source type LNC-5LP60-S325+56CR-520-13-O11-A7.5-HP-4 has a fan angle of 62°.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 18 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics [type HP](#) with micro-controller for control of the laser output power. It is a low noise laser source (0.1 % RMS,@<1 MHz) with reduced coherence length and operates mode-hopping free. Due to the reduced coherence length the speckle contrast might be lowered. Please note that this effect is smaller for smaller lines and spots. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

## TECHNICAL DATA

LNC-5LP60-S325+56CR-520-13-O11-A7.5-HP-4

|                                      |  |                 |
|--------------------------------------|--|-----------------|
| <b>Series</b>                        | 5LP                                      |                 |
| <b>Order Code</b>                    | LNC-5LP60-S325+56CR-520-13-O11-A7.5-HP-4 |                 |
| <b>Line profile</b>                  | Gaussian Intensity Distribution          |                 |
| <b>Line type</b>                     | Laser Micro Line                         |                 |
| <b>Wavelength</b>                    | 520 +10/-5 nm                            |                 |
| <b>Laser output power</b>            | 13 mW                                    |                 |
| <b>Laser safety class</b>            | 3B                                       |                 |
| <b>Fan angle <math>\alpha</math></b> | 62 deg                                   |                 |
| <b>Focussing range</b>               | 260-430 mm                               |                 |
| <b>Working distance</b>              | 317 mm                                   |                 |
| <b>Line length</b>                   | 375 mm                                   |                 |
| <b>Line width</b>                    | 0.156 mm                                 |                 |
| <b>Rayleigh range</b>                | 73.8 mm                                  |                 |
| <b>Edge intensity</b>                | 18 %                                     |                 |
| <b>Diameter laser module</b>         | 25/28 mm                                 |                 |
| <b>Module length</b>                 | 98.6 mm                                  |                 |
| <b>Installation length</b>           | 415.6 mm                                 |                 |
| <b>Cable length</b>                  | 1.5 m                                    |                 |
| <b>Connector type</b>                | Lumberg SV40 IEC 61076-2-106             |                 |
| <b>Supply voltage</b>                | 12 $\pm$ 0.5 V                           |                 |
| <b>Max. current consumption</b>      | 0.3 A                                    |                 |
| <b>Working temperature</b>           | 15 - 40 °C                               |                 |
| <b>Modulation inputs</b>             | Analog                                   | TTL             |
| <b>Input resistance</b>              | 9 kOhm                                   | 9 kOhm          |
| <b>Max. modulation frequency</b>     | 0.001 kHz                                | 300 kHz         |
| <b>Modulation delay ON/OFF</b>       | 2000/500 $\mu$ s                         | 0.5/0.2 $\mu$ s |
| <b>Rise / Fall time</b>              | 200000/200000 $\mu$ s                    | 0.8/0.3 $\mu$ s |

Noise (< 1 MHz RMS)

0.1 %

## DOWNLOADS



[930412000133.pdf](#)

## ACCESSORIES

|                 |  |
|-----------------|--|
| 50HD-15         | Hex key WS 1.5   |
| 9D-12           | Screwdriver WS 1.2                                     |
| 13MK-25-36-10-F | Mounting Console with flat base plate                  |
| 13MK-25-36-10-M | Mounting Console with base plate with dovetail profile |
| PS120516E       | Power Supply 12 V                                      |

## RELATED PRODUCTS

|                                  |   |
|----------------------------------|---|
| LASER MODULES<br>SERIES LNC-5LPM | <ul style="list-style-type: none"> <li>▪ Macro Line, <b>large</b> fan angle</li> <li>▪ Gaussian intensity distribution</li> <li>▪ Extended depth of focus</li> <li>▪ Low noise</li> </ul> |
| LASER MODULES<br>SERIES 5LP      | <ul style="list-style-type: none"> <li>▪ Micro Line, <b>large</b> fan angle</li> <li>▪ Gaussian intensity distribution</li> </ul>   |
| LASER MODULES<br>SERIES LNC-13LN | <ul style="list-style-type: none"> <li>▪ Micro Line, <b>small</b> fan angle</li> <li>▪ Uniform intensity distribution</li> <li>▪ Thin lines</li> <li>▪ Low noise</li> </ul>               |
| LASER MODULES<br>SERIES LNC-5LM  | <ul style="list-style-type: none"> <li>▪ Micro Line, <b>small</b> fan angle</li> <li>▪ Gaussian intensity distribution</li> <li>▪ Low noise</li> </ul>                                    |

This is a printout of the page [https://sukhamburg.com/products/details/LNC-5LP60-S325\\_56CR-520-13-O11-A7\\_5-HP-4](https://sukhamburg.com/products/details/LNC-5LP60-S325_56CR-520-13-O11-A7_5-HP-4) from 12/5/2023

## CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

[info@sukhamburg.de](mailto:info@sukhamburg.de)

[www.sukhamburg.com](http://www.sukhamburg.com)

## LEGAL NOTICE

**Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.**

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)