LNC-5LP60-S325+56CR-685-18-H13-A8-H-6


Low Noise Micro Line Generator with a large fan angle



FEATURES

Laser line with a large fan angle and Gaussian intensity distribution.

- Line length: 375 mm
- Line width: 126 μm
- Wavelength: 685 nm
- Working distance: 317 mm
- Low noise laser module (0.1 % RMS, @<1 MHz)
- Micro Line Generator for small laser line widths and high power density in the focal plane
- Low noise, low coherence laser module (typ. < 0.15 % of P₀ (RMS, Bandwidth < 1 MHz))



DESCRIPTION

The laser diode beam source type LNC-5LP60-S325+56CR-685-18-H13-A8-H-6 has a fan angle of 62°.

The intensity profile is Gaussian in line direction clipped by an aperture with an edge intensity of 14 %. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics <u>type H</u> for control of the laser output power. It is a low noise laser source (0.1 % RMS,@<1 MHz) with reduced coherence length and operates mode-hopping free. Due to the reduced coherence length the speckle contrast might be lowered. Please note that this effect is smaller for smaller lines and spots. The output power can be controlled using the <u>modulation input ports (TTL and analog)</u> or manually using the potentiometer.

The working distance can be adjusted by adjusting the focus setting. Please note that beam parameters like line length and line width increase proportionally to the working distance. A fine-adjustment of the distance between laser and target is recommended for fine-focusing.

TECHNICAL DATA

LNC-5LP60-S325+56CR-685-18-H13-A8-H-6

Series		5LP
Order Code	LNC-5LP60-S325+56CR-685-18-H13-A8-H-6	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Micro Line	
Wavelength	685 +10/-10 nm	
Laser output power	18 mW	
Laser safety class		3B
Fan angle α	62 deg	
Focussing range	260-430 mm	
Working distance		317 mm
Line length		375 mm
Line width	0.126 mm	
Rayleigh range	36.5 mm	
Edge intensity	14 %	
Diameter laser module	25/28 mm	
Module length		98.6 mm
Installation length	415.6 mm	
Cable length		1.5 m
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.25 V	
Max. current consumption	0.25 A	
Working temperature		0 - 40 °C
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	100 kHz	100 kHz
Modulation delay ON/OFF	2/0.3 µs	1.5/0.1 μs
Rise / Fall time	1/1 µs	1/1 µs



Noise (< 1 MHZ RMS)

0.1%

DOWNLOADS



930412000133.pdf

ACCESSORIES

50HD-15	Hex key WS 1.5
9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS051003E	Power Supply 5 V

RELATED PRODUCTS

LASER MODULES SERIES LNC-5LPM	 Macro Line, large fan angle Gaussian intensity distribution Extended depth of focus Low noise
LASER MODULES SERIES 5LP	 Micro Line, large fan angle Gaussian intensity distribution
LASER MODULES SERIES LNC-13LN	 Micro Line, small fan angle Uniform intensity distribution Thin lines Low noise
LASER MODULES SERIES LNC-5LM	 Micro Line, small fan angle Gaussian intensity distribution

Low noise



DATA SHEET

This is a printout of the page <u>https://sukhamburg.com/products/details/LNC-5LP60-S325_56CR-685-18-H13-A8-H-6</u> from 4/26/2024

CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]

