

LNC-5LT-75-2+56CM-405-37-X15-A7.5-HP-4

Semi-telecentric Micro Line Generator



FEATURES

Semi-telecentric laser line with constant line length of 2.4 mm.

- Line length: 2.4 mm
- Line width: 9 μm
- Wavelength: 405 nm
- Working distance: 74 mm
- Low noise laser module (0.1 % RMS, @<1 MHz)

- Micro Line Generator for small laser line widths and high power density in the focal plane
- Low noise, low coherence laser module (typ. < 0.15 % of P_0 (RMS, Bandwidth < 1 MHz))



DESCRIPTION

The laser diode beam source type LNC-5LT-75-2+56CM-405-37-X15-A7.5-HP-4 produces a semi-telecentric laser line with 2.4 mm line length. In this case the line length is given on the 13.5%-level. The intensity profile is Gaussian in line direction and the line is truncated at 4.8 mm. The line width is constant along the laser line. Across the laser line the intensity distribution is Gaussian.

The laser has integrated electronics [type HP](#) with micro-controller for control of the laser output power. It is a low noise laser source (0.1 % RMS, @<1 MHz) with reduced coherence length and operates mode-hopping free. Due to the reduced coherence length the speckle contrast might be lowered. Please note that this effect is smaller for smaller lines and spots. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

For this laser type the working distance is fixed. A fine-adjustment of the distance between laser and target is recommended for fine-focusing in order to achieve minimal line width.

TECHNICAL DATA

LNC-5LT-75-2+56CM-405-37-X15-A7.5-HP-4

Series	5LT	
Order Code	LNC-5LT-75-2+56CM-405-37-X15-A7.5-HP-4	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Micro Line	
Wavelength	405 +5/-5 nm	
Laser output power	37 mW	
Laser safety class	3B	
Focussing range	74-74 mm	
Working distance	74 mm	
Line length	2.4 mm	
Line width	0.009 mm	
Rayleigh range	0.317 mm	
Edge intensity	10 %	
Diameter laser module	25/28 mm	
Module length	82.6 mm	
Installation length	186.6 mm	
Cable length	1.5 m	
Connector type	Lumberg SV40 IEC 61076-2-106	
Supply voltage	12 ± 0.5 V	
Max. current consumption	0.3 A	
Working temperature	15 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	9 kOhm	9 kOhm
Max. modulation frequency	0.001 kHz	300 kHz
Modulation delay ON/OFF	2000/500 µs	0.5/0.2 µs
Rise / Fall time	200000/200000 µs	0.8/0.3 µs
Noise (< 1 MHz RMS)	0.1 %	

DOWNLOADS



[930412000094.pdf](#)

ACCESSORIES

9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS120516E	Power Supply 12 V

RELATED PRODUCTS

LASER MODULES SERIES LNC-5LTM-2

- Semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**
- Extended depth of focus
- Low noise

LASER MODULES SERIES 5LTM-2

- Semi-telecentric Macro Line
- Gaussian intensity distribution
- Constant line length ca. **2 mm**
- Extended depth of focus

LASER MODULES SERIES LNC-13LT

- Semi-telecentric Micro Line
- Uniform intensity distribution
- Constant line length **15 mm**
- Low noise

LASER MODULES SERIES LNC-5LT-1

- Semi-telecentric Micro Line
- Gaussian intensity distribution
- Constant line length ca. **4.8 mm**
- Low noise

This is a printout of the page https://sukhamburg.com/products/details/LNC-5LT-75-2_56CM-405-37-X15-A7_5-HP-4
from 12/5/2023

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)