

LNC-5LTM-75-22+56CM-639-5-H18-A8-H-6

Semi-telecentric Macro Line Generator



FEATURES

Semi-telecentric laser line with constant line length of 2.4 mm and extended depth of focus.

- Line length: 2.4 mm
- Line width: 40 μm
- Wavelength: 639 nm
- Working distance: 68 mm
- Depth of focus: 4 mm
- Low noise laser module (0.1 % RMS, @<1 MHz)

- Macro Line Generator for extended depth of focus
- Low noise, low coherence laser module (typ. < 0.15 % of P_0 (RMS, Bandwidth < 1 MHz))



DESCRIPTION

The laser diode beam source type LNC-5LTM-75-22+56CM-639-5-H18-A8-H-6 produces a semi-telecentric laser line with 2.4 mm line length. In this case the line length is given on the 13.5%-level. The intensity profile is Gaussian in line direction and the line is truncated at 4.8 mm. The line width is constant along the laser line. Across the laser line the intensity distribution is approx. Gaussian.

The laser has integrated electronics [type H](#) for control of the laser output power. It is a low noise laser source (0.1 % RMS, @<1 MHz) with reduced coherence length and operates mode-hopping free. Due to the reduced coherence length the speckle contrast might be lowered. Please note that this effect is smaller for smaller lines and spots. The output power can be controlled using the [modulation input ports \(TTL and analog\)](#), or manually using the potentiometer.

For this laser type the working distance is fixed. A fine-adjustment of the distance between laser and target is recommended for fine-focusing in order to achieve minimal line width.

TECHNICAL DATA

LNC-5LTM-75-22+56CM-639-5-H18-A8-H-6

Series	5LTM	
Order Code	LNC-5LTM-75-22+56CM-639-5-H18-A8-H-6	
Line profile	Gaussian Intensity Distribution	
Line type	Laser Macro Line	
Wavelength	639 +10/-10 nm	
Laser output power	5 mW	
Laser safety class	3R	
Focussing range	68-68 mm	
Working distance	68 mm	
Line length	2.4 mm	
Line width	0.04 mm	
Depth of focus	4 mm	
Edge intensity	40 %	
Diameter laser module	25/28 mm	
Module length	88 mm	
Installation length	186 mm	
Cable length	1.5 m	
Connector type	Lumberg SV50 IEC 61076-2-106	
Supply voltage	5 ± 0.2 V	
Max. current consumption	0.25 A	
Working temperature	0 - 40 °C	
Modulation inputs	Analog	TTL
Input resistance	22 kOhm	22 kOhm
Max. modulation frequency	100 kHz	100 kHz
Modulation delay ON/OFF	2/0.3 µs	1.5/0.1 µs
Rise / Fall time	1/1 µs	1/1 µs
Noise (< 1 MHz RMS)	0.1 %	

ACCESSORIES

9D-12	Screwdriver WS 1.2
13MK-25-36-10-F	Mounting Console with flat base plate
13MK-25-36-10-M	Mounting Console with base plate with dovetail profile
PS051003E	Power Supply 5 V

RELATED PRODUCTS

LASER MODULES SERIES LNC-5LT-2	<ul style="list-style-type: none">▪ Semi-telecentric Micro Line▪ Gaussian intensity distribution▪ Constant line length ca. 2 mm▪ Low noise
LASER MODULES SERIES 5LTM-2	<ul style="list-style-type: none">▪ Semi-telecentric Macro Line▪ Gaussian intensity distribution▪ Constant line length ca. 2 mm▪ Extended depth of focus
LASER MODULES SERIES LNC-13LTM	<ul style="list-style-type: none">▪ Semi-telecentric Macro Line▪ Uniform intensity distribution▪ Constant line length 15 mm▪ Extended depth of focus▪ Low noise
LASER MODULES SERIES LNC-5LTM-1	<ul style="list-style-type: none">▪ Semi-telecentric Macro Line▪ Gaussian intensity distribution▪ Constant line length ca. 4.8 mm▪ Extended depth of focus▪ Low noise

This is a printout of the page https://sukhamburg.com/products/details/LNC-5LTM-75-22_56CM-639-5-H18-A8-H-6 from 4/26/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)