

Switchbox PS051007E

Power Supply 5 V for laser modules with RS232 interface



FEATURES

Power supply for all Laser Modules with 5 V supply voltage and with RS232 interface

DESCRIPTION

Power supply for all Laser Modules with 5 V supply voltage with RS232 interface.
The power supply is also suitable if the laser is operated together with a [switchbox](#).

TECHNICAL DATA

Switchbox PS051007E

Input

Input voltage	100 - 240 VAC
Input current	max. 0.5 A
Input frequency	50 - 60 Hz
Input connector	IEC320-C14

Output

Output power	13 W
Output voltage	5 VDC
Output current	2.6 A
Output connector	7-pin (female), IEC 61076-2-106

Output connector type	Lumberg KV70 (female)
Output connector compatibility	SV70 (male)
Cable type	1.8 m shielded
Dimensions	86.5 x 47.4 x 32 mm
Weight	223 g
RoHS compliant	yes

ACCESSORIES

PC150DE Power Cord, Europe

PC150US Power Cord, US

PC150UK Power Cord, UK

RELATED PRODUCTS

SBS070701-USB For laser diode modules with RS232 interface

This is a printout of the page <https://sukhamburg.com/products/details/PS051007E> from 4/24/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212

22525 Hamburg

Germany

Tel: +49 40 85 39 97-0

Fax: +49 40 85 39 97-79

info@sukhamburg.de

www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)